Previous Versions: 11/18/04, 04/05/99, 08/17/94 and 08/18/00

Item No. 102S Clearing and Grubbing

### 102S.1 Description

This item shall govern the removal and disposal of all trees, stumps, brush, roots, shrubs, vegetation, logs, rubbish and other objectionable material.

This specification is applicable for projects or work involving either inch-pound or SI units. Within the text the inch-pound units are given preference followed by SI units shown within parentheses.

#### 102S.2 Submittals

The submittal requirements of this specification item may include:

- A. A permit when utility adjustments are made in the right-of-way, and
- B. A plan for removal and deposition of all clearing and grubbing materials and debris.

#### 102S.3 Construction Methods

Prior to commencement of this work, all required erosion control and tree protection measures indicated on the Drawings shall be in place. The existing utilities shall be located and protected as specified in the Standard Contract Documents, Section 00700, "General Conditions" and/or indicated on the Drawings. A permit shall be required when utility adjustments are to be made in preparation for construction in the right-of-way, as specified in Section 5.2.0 of the City of Austin Utilities Criteria Manual.

Areas within the construction limits indicated on the Drawings shall be cleared of all trees, stumps, brush, etc., as defined in section 102S.1; except trees or shrubs scheduled for preservation which shall be carefully trimmed as directed, in accordance with Item No. 610S, " Preservation of Trees and Other Vegetation" and shall be protected from scarring, barking or other injuries during construction operations. All exposed cuts over 2 inches (50 millimeters) in diameter, exposed ends of pruned limbs or scarred bark shall be treated with an approved asphalt material within 24 hours of the pruning or injury.

Construction equipment shall not be operated nor construction materials stockpiled under the canopies of trees, unless otherwise indicated on the Drawings and/or specified in the Contract Documents. Excavation or embankment materials shall not be placed within the drip line of trees until tree wells are constructed.

### \* See Modifications for additional information

Within the construction limits or areas indicated, all obstructions, stumps, roots, vegetation, abandoned structures, rubbish and objectionable material shall be removed to the following depths:

1. In areas to receive 6 inches (150 mm) or more embankment, a minimum of 12 inches (300 mm) below natural ground.

Previous Versions: 11/18/04, 04/05/99, 08/17/94 and 08/18/00

- 2. In areas to receive embankment less than 6 inches (150 mm), a minimum of 18 inches (450 mm) below the lower elevation of embankment, structure or excavation.
- 3. In areas to be excavated a minimum of 18 inches (450 mm) below the lower elevation of the embankment, structure or excavation.
- 4. In all other areas a minimum of 12 inches (300 mm) below natural ground.

Holes remaining after removal of all obstructions, objectionable material, trees, stumps, etc. shall be backfilled with select embankment material and compacted by approved methods. All cleared and grubbed material shall be disposed of in a manner satisfactory to the Engineer or designated representative. Unless otherwise provided, all materials as described above shall become the property of the Contractor and removed from the site and disposed of at a permitted disposal site.

Burning materials at the site shall conform to Standard Contract Document Section 01550, "Public Safety and Convenience".

#### 102S.4 Measurement

"Clearing and Grubbing", when included in the contract as a pay item, will be measured by the acre (hectare: 1 hectare is equal to 2.471 acres), 100 foot (100 feet is equal to 30.5 meters) stations or lump sum, regardless of the width of the right of way.

#### 102S.5 Payment

The work and materials presented herein will not be paid for directly, but shall be included in the unit price bid for the item of construction in which this item is used, unless specified as a separate pay item in the contract bid form. When included for payment, it shall be paid for at the unit bid price for "Clearing and Grubbing". This price shall include full compensation for all work herein specified, including the furnishing of all materials, equipment, tools, labor and incidentals necessary to complete the Work.

Payment, when included as a contract pay items, will be made under one of the following:

Pay Item No. 102S-A: Clearing and GrubbingPer Acre.Pay Item No. 102S-B: Clearing and GrubbingPer 100 foot Station.Pay Item No. 102S-C: Clearing and GrubbingLump Sum.

#### End

#### **SPECIFIC CROSS REFERENCE MATERIALS**

Specification Item 102S, "CLEARING AND GRUBBING"

City of Austin Standard Contract Documents

Designation Description

00700 General Conditions

01550 Public Safety and Convenience

City of Austin Utilities Criteria Manual
Designation Description

Section 5.2.0 Permit for Excavation in the Public Right-of-Way

Previous Versions: 11/18/04, 04/05/99, 08/17/94 and 08/18/00

#### City of Austin Standard Specifications

DesignationDescriptionItem No. 110SStreet ExcavationItem No. 111SExcavation

Item No. 610S Preservation of Trees and Other Vegetation

#### **RELATED** CROSS REFERENCE MATERIALS

The Code of the City of Austin, Code of Ordinances, Volume 1

<u>Designation</u>
Article 14-11-181

<u>Description</u>
Permit Required

Article 14-11-189 Conditions for Permit Issuance

Article 14-11-190 Excavation Sequence and Permit Term

#### City of Austin Standard Contract Documents

<u>Description</u>

01500 Temporary Facilities

#### City of Austin Standard Specifications

<u>Designation</u>	Description
Item No. 101S	Preparing Right of

Item No. 101S Preparing Right of Way

Item No. 104S Removing Portland Cement Concrete

Item No. 120S Channel Excavation

Item No. 132S Embankment

Item No. 201S Subgrade Preparation

Item No. 203S Lime Treatment for Materials In Place

Item No. 204S Portland Cement Treatment for Materials In Place

Item No. 230S Rolling (Flat Wheel)
Item No. 232S Rolling (Pneumatic Tire)
Item No. 234S Rolling (Tamping)
Item No. 236S Rolling (Proof)

Item No. 602S Sodding for Erosion Control Item No. 604S Seeding for Erosion Control

Item No. 622S Diversion Dike

Item No. 628S Sediment Containment Dikes

Item No. 642S Silt Fence

#### City of Austin Standard Details

<u>Designation</u>	<u>Description</u>
610S-1	Tree Protection Fence Locations
610S-2	Tree Protection Fence, Type B Chainlink
610S-3	Tree Protection Fence, Type B Wood
610S-4	Tree Protection Fence, Modified Type A
610S-5	Tree Protection Fence, Modified Type B
621S-1	Diversion
622S-1	Diversion Dike
624S-1	Earth Outlet Sediment Trap

### **RELATED** CROSS REFERENCE MATERIALS-Continued

Specification 102S, "CLEARING AND GRUBBING"

### City of Austin Standard Details

Designation

625S-1	Grade Stabilization Structure
627S-1	Grass Lined Swale

627S-2 Grass Lined Swale With Stone Center

628S Triangular Sediment Filter Dike

Description

628S-1 Hay Bale Dike

# Current Version08/20/07 City of San Marcos Adopted 05/15/2014 Revised 06/01/2018

Previous Versions: 11/18/04, 04/05/99, 08/17/94 and 08/18/00

d 06/01/2018	
ed 06/01/2018 629S-1	Brush Berm
630S-1	Interceptor Dike
631S-1	Interceptor Swale
632S-1	Storm Inlet Sediment Trap
633S-1	Landgrading
634S-1	Level Spreader
635S-1	Perimeter Dike
636S-1	Perimeter Swale
637S-1	Pipe Slope Drain (Flexible)
637S-2	Pipe Slope Drain (Flexible)
638S-1	Pipe Outlet Sediment Trap
639S-1	Rock Berm
641S-1	Stabilized Construction Entrance
642S-1	Silt Fence
643S-1	Stone Outlet Structure
644S-1	Stone Outlet Sediment Trap

# Texas Department of Transportation: <u>Standard Specifications for Construction and</u>

## Maintenance of Highways, Streets, and Bridges

<u>Designation</u>	Description
Item No. 100	Preparing Right of Way
Item No. 110	Excavation
Item No. 112	Subgrade Widening
Item No. 132	Embankment
Item No. 150	Blading
Item No. 158	Specialized Excavation Work
Item No. 160	Furnishing and Placing Topsoil
Item No. 164	Seeding for Erosion Control
Item No. 204	Sprinkling
Item No. 210	Rolling (Flat Wheel)
Item No. 211	Rolling (Tamping)
Item No. 213	Rolling (Pneumatic Tire)
Item No. 260	Lime Treatment for Materials Used as Subgrade (Road Mixed)
Item No. 265	Lime-Fly Ash (LFA) Treatment for Materials Used as Subgrade

## Texas Department of Transportation:

# Manual of Testing Procedures

<u>Designation</u>	Description
Tex-103-E	Determination of Moisture Content of Soil Materials
Tex-105-E	Determination of Plastic Limit of Soils
Tex-106-E	Method of Calculating the Plasticity Index of Soils
Tex-114-E	Laboratory Compaction Characteristics and Moisture Density
	Relationship of Subgrade & Embankment Soil
Tex-115-E	Field Method for Determination of In-Place Density of Soils and
	Base Materials